

DR-6255

CSN SELECT Desktop Enrollment Reader (Rev. A)



The DR-6255 is a desktop smart card CSN enrollment reader with a USB interface for use when enrolling user credentials to access control software such as Rosslare's AxTraxNG™. The reader is part of the CSN SELECT family of multi-credential technology contactless smart card (13.56 MHz) readers. This reader has the flexibility to read the Card Serial Number (CSN) from many smart card RFID standards implementations including ISO14443A/B, ISO15693, and ISO18092, perfect for transitioning from one technology to another. The reader has a sleek and modern design, and is powered by the USB port itself for easy and convenient installation.

GENERAL DESCRIPTION

The DR-6255 appears as a COM port device and can be used for any application. The standard reader is configured to read the CSN of the most popular smart cards in the security industry and output the CSN as a Wiegand 26-Bit output. A tri-color LED indicator and a buzzer provide feedback for successful card reads.

MAIN FEATURES

- Read the CSN from the following smart cards:
 - ISO14443A - MIFARE® Ultralight® Nano / Ultralight EV1/ Ultralight C
 - MIFARE Classic® / Classic EV1
 - MIFARE Plus® S / SE / X / EV1
 - MIFARE DESFire® EV1 / EV2
 - NFC N-TAG / Card Emulation
 - ISO14443B – China National ID
 - ISO15693 – HID® iClass®, PicoPass, iCode, LEGIC
 - ISO18092 – SONY® FeliCa® (Hong Kong Octopus)

- Appears as a COM port device when connected and could be used for any application
- The standard reader outputs the Wiegand CSN data in Wiegand 26-Bit format. Other Wiegand formats are selectable using the DR-6255 Hardware Configuration Tool PC software

PROFESSIONAL GRADE FEATURES

- Tri-color LED and built-in buzzer
- USB 2.0 compliant and USB powered
- Wiegand output format can be configured using a PC software, including Wiegand 26-Bit, 32-Bit, 32-Bit (reverse), 34-Bit, 40-Bit, 56-Bit, and 64-Bit outputs
- Uses standard drivers that support the following operating systems:
 - Windows XP (32-Bit and 64-Bit)
 - Windows 7 (32-Bit and 64-Bit)
 - Windows 8 (32-Bit and 64-Bit)
 - Windows 10 (32-Bit and 64-Bit)

SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

■ Operating Voltage Range	5 VDC (USB powered)
■ Standby Current @ 5 V	90 mA
■ Maximum Current @ 5 V	30 mA
■ Read Range*	5 cm (2 in.)
■ Reader Data Output Format	Appears a COM port device when connected to a PC. The standard reader outputs the Wiegand CSN data in Wiegand 26-Bit format. Other Wiegand formats are selectable using the DR-6255 Hardware Configuration Tool PC software.
■ USB Cable Length	150 cm (59 in.)

ENVIRONMENTAL SPECIFICATIONS

■ Operating Environment	Indoor use
■ Operating Temperature Range	0°C to 63°C (32°F to 145°F)
■ Operating Humidity Range	0% to 95% (non-condensing)

MECHANICAL SPECIFICATIONS

■ Dimensions (H x W x D)	123.0 x 70.0 x 16.2 mm (4.9 x 2.8 x 0.7 in.)
■ Weight	130 g (4.6 oz.)

SYSTEM COMPONENTS

Compatible with a Rosslare's AxTraxNG™, as well as many third-party access control software.

PRODUCT WARRANTY

2-Year Limited Product Warranty

* Measured using a Rosslare MIFARE Classic EV1 (ISO Card). Read range with other credential technologies may vary. Range also depends on electrical environment and proximity to metal.

ABOUT ROSSLARE SECURITY

Rosslare Security Products manufactures and markets high-quality security products via its worldwide offices and channel partners. Since 1980, Rosslare has offered high-quality systems for enterprise, small business, and residential applications. With Rosslare, you receive the best of all worlds: world-class product engineering and design; professional customer service spanning the globe; and the quality and affordability of a vertically integrated and self-owned manufacturing facility. Our expansive product range features much more than access control solutions and guard patrol management systems; we also offer applications software – such as License Plate Recognition, Time & Attendance, and DVR/alarm integration.

www.rosslaresecurity.com

MIFARE, Ultralight, Classic, Plus, DESFire and iCode are registered trademarks of NXP B. V.
 iClass is a registered trademark of HID
 FeliCa is a registered trademark of Sony
 All data contained herein subject to change without notice

5505-0295101-03
 Copyright © Rosslare

