



## M04SW WEDGE CAMERA HOUSING

The M04 range of housings are designed to accommodate a wide range of analogue and IP addressable CCD camera and lens combinations. The M04SW is an outdoor wedge housing with clear internal space to accommodate camera bodies up to 240mm in length. The M04LW model is also available, offering 308mm long internal camera space.

The IP54 rated M04SW housing features light weight construction and incorporates a 6mm float glass lens. Polycarbonate, acrylic or quartz optical glass lenses are also available.

The Quartz optical glass lens offers excellent clarity as it is mounted parallel to the ground, eliminating distortion which is evident when zoom lenses are used.

### APPLICATIONS

The M04 series is ideal for use in car parks, public transport areas, railway platforms, under eaves, tunnels and walkways.

This ceiling mounted wedge housing is suitable for indoor and outdoor environments.

### FEATURES

- Housing body swings down from ceiling for ease of access and installation.
- Rugged design for high traffic outdoor areas under eaves.
- Durable 6mm glass lens with optional alternatives for optimum clarity and minimal distortion.
- Economic housing suitable for transport or commercial projects - available in two sizes to accommodate most analogue and IP addressable CCD camera and lens combinations.

### SPECIFICATIONS

|                 |                                                                                                                                                  |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Construction    | 1mm & 2mm zinc anneal.                                                                                                                           |
| Finish          | Dulux powder coat in Off-White Satin finish.                                                                                                     |
| Lens            | 6mm glass. Optional acrylic, GE Lexan polycarbonate or Quartz glass optical lens for high resolution and long zoom camera and lens combinations. |
| Cable Entry     | 2 x 20mm cable entry at rear.                                                                                                                    |
| Access          | 2 x M4 post cap security screws.                                                                                                                 |
| Electrical      | Optional heater thermostat - 24 VAC 50Hz 11 Watts. Optional fan - 24 VAC 50Hz 3.2 Watts.                                                         |
| Max Camera Size | Camera and lens up to 240mm long.                                                                                                                |
| Weight          | TBA                                                                                                                                              |

### ALSO AVAILABLE

**M04LW** variation accommodates lenses up to 308mm in length.



## DIMENSIONS

