



1055-N

Recessed mount magnetic contact with bare magnet

1055 series

The Sentrol 1055 series are ideal for mounting in aluminum door and window tracks and sliding glass door tracks. Recess mount in wood doors and windows. The recessed magnetic contact is only 0.64 cm in diameter. Adhesive required to security mounting.

Durability and dependability

The Sentrol high performance magnetic contacts have been designed to facilitate installation and ensure durability and dependability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory, 100% of the time.

High quality components and materials

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.



Details

- Perfect for window screen protection
- Versatile compact size
- Attractive, added security of recessed installation

1055-N

Recessed mount magnetic contact with bare magnet

Technical specifications

Gap distance (max)

13 mm

Connections

30 cm wire leads

Contact

NC

Supervised loop

No

Dimensions (Ø x L)

Contact Ø 6 x 29 mm

Magnet Ø 6 x 32 mm

Color

White



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 23 July 2021 - 10:31