

1078 series steel door contacts

recessed steel door magnetic contacts with wire leads
1 in. dia.

The 1078 series recessed contacts are designed specifically for use in the steel doors commonly found in commercial building applications.

The unique housing design of the 1078 contact features a rugged unibody construction with flexible ribbed sides for quick, secure installation without gluing. The magnet housing isolates the magnet from the surrounding steel for maximum gap distances.

A wide gap model is available to protect against false alarms from loose-fitting doors.



Specifications

Voltage:	1078: 100 VAC/VDC max.; 1076: 30 VAC/VDC max.
Current:	1078: 0.5 A max.; 1076: 0.25 A max.
Power:	1078: 7.5 W max.; 1076: 3.0 W max.
Loop type:	1078: Closed; 1076: Open or Closed
Electrical configuration:	1078: Normally open; 1076: SPDT; 1076D: DPDT
Lead type:	1 ft. #22 wire
Gap distance:	1078/1076: Up to 1/2 in. 1078W/1076W: Up to 1 in.
Dimensions:	1.125 in. L x 1.125 in. dia. (29 x 29 mm)
Housing:	Flame retardant ABS plastic
Color:	White, brown, gray
Regulatory:	UL, CUL

Ordering information

1078N-10PKG (-50BOX)	Recessed steel door contact w/ leads, 1 in. dia., 1/2 in. gap size, closed loop, white, pk/10 (pk/50 -50BOX)
1078M-10PKG (-50BOX)	Recessed steel door contact w/ leads, 1 in. dia., 1/2 in. gap size, closed loop, brown, pk/10 (pk/50 -50BOX)
1078WN-10PKG (-50BOX)	Recessed steel door contact w/ leads, 1 in. dia., 1 in. gap size, closed loop, white, pk/10 (pk/50 -50BOX)
1078WM-10PKG (-50BOX)	Recessed steel door contact w/ leads, 1 in. dia., 1 in. gap size, closed loop, brown, pk/10 (pk/50 -50BOX)
1078WG-10PKG (-50BOX)	Recessed steel door contact w/ leads, 1 in. dia., 1 in. gap size, closed loop, gray, pk/10 (pk/50 -50BOX)
1076N-10PKG (-50BOX)	Recessed steel door contact w/ leads, 1 in. dia., 1/2 in. gap size, SPDT, white, pk/10 (pk/50 -50BOX)
1076M-10PKG (-50BOX)	Recessed steel door contact w/ leads, 1 in. dia., 1/2 in. gap size, SPDT, brown, pk/10 (pk/50 -50BOX)
1076G-10PKG (-50BOX)	Recessed steel door contact w/ leads, 1 in. dia., 1/2 in. gap size, SPDT, gray, pk/10 (pk/50 -50BOX)
1076W-N	Recessed steel door contact w/ leads, 1 in. dia., 1 in. gap size, SPDT, white
1076W-M	Recessed steel door contact w/ leads, 1 in. dia., 1 in. gap size, SPDT, brown
1076H-N	Recessed steel door contact w/ leads, 1 in. dia., 1/2 in. gap size, SPDT, biased for higher security, white
1076DN-10PKG (-50BOX)	Recessed steel door contact w/ leads, 1 in. dia., 1/2 in. gap size, DPDT, white, pk/10 (pk/50 -50BOX)
1076DM-10PKG (-50BOX)	Recessed steel door contact w/ leads, 1 in. dia., 1/2 in. gap size, DPDT, brown, pk/10 (pk/50 -50BOX)
1076DG-10PKG (-50BOX)	Recessed steel door contact w/ leads, 1 in. dia., 1/2 in. gap size, DPDT, gray, pk/10 (pk/50 -50BOX)

- Special design for steel mounting
- Rugged unibody construction for maximum durability and reliability
- Recessed installation makes contacts less visible and more difficult to detect and defeat
- Available wider gap distance helps prevent false alarms caused by loose-fitting doors and windows
- High Security models available
- Rare Earth Magnet designed for steel door with top channel available
- UL listed for specific fire doors

