



# 1285T-N

## Design surface mount contact with screw terminals

### Designer styled with screw terminals

---

The Sentrol 1285T series surface mount magnetic contacts are ideal for residential and commercial applications where terminal connections are preferred. The unit features Sems style terminals that have self-lifting washers and captured screws to prevent the screw from backing out. The screw have combination heads that accept either Phillips or flat blade drivers.

### Easy installation

---

The terminals are angled away from the mounting surface to allow for quick and easy installation. Snap-on covers conceal the terminals and mounting screws for a clean professional appearance.

### Durability and dependability

---

The Sentrol high performance magnetic contacts have been designed to facilitate installation and ensure durability and dependability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory, 100% of the time.

### High quality components and materials

---

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.

### Built-in end of line 3K3 resistors

---

For seamless connection to the control panel, the 1285T series contains also contacts with built-in end of line resistors. The 2 resistors with a value of 3K3 each are configured in double end of line configuration, allowing a quick, professional and clean installation.



### Details

---

- Ideal for residential and commercial applications
- Angled clamping terminals for fast, easy connection
- Modern, low-profile design
- Convenient surface mounting; Combo head screws for quick termination
- Versions with built-in 3K3 resistors available

# 1285T-N

## Design surface mount contact with screw terminals

### Technical specifications

---

#### Gap distance (max)

---

19 mm

---

#### Connections

---

Screw terminals

---

#### Contact

---

NC

---

#### Supervised loop

---

No

---

#### Dimensions (L x W x H)

---

Contact	65 x 18 x 14 mm
---------	-----------------

---

Magnet	65 x 15 x 14 mm
--------	-----------------

---

#### Color

---

White

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 23 July 2021 - 10:31