

2302A-L

Curtain door overhead contact with stainless steel armored cable

Curtain door magnetic contact

The Sentrol 2302A-L curtain door magnetic contact is for use in the rigorous environments of commercial and industrial installations. With its special design it's the ideal solution for curtain style doors to allow maximum security and safety. The reed switch assembly is fully encased in Sentrol's exclusive polyurethane potting material to prevent damage due to moisture or humidity.

Durability and dependability

The Sentrol high performance magnetic contacts have been designed to facilitate installation and ensure durability and dependability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory, 100% of the time.

High quality components and materials

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.



Details

- Designed specifically for curtain style overhead doors
- Interlocking mounting bracket
- Magnet mounts in door channel
- Fits most doors
- Reduced installation time
- Mounting hardware included

2302A-L

Curtain door overhead contact with stainless steel armored cable

Technical specifications

Gap distance (max)

76 mm

Connections

60 cm stainless steel armored cable

Contact

NC

Supervised loop

No

Dimensions (L x W x H)

Contact	92 x 89 x 16 mm
---------	-----------------

Magnet	108 x 25 x 19 mm
--------	------------------

Color

Aluminum



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 23 July 2021 - 10:31