SMART4355G





D7PX11 – Contact Block Screw

800FM-F3 Button Only



Plate Specifications

Plate Material : STAINLESS STEEL
Plate Color : SILVER
Plate style : FLAT
Plate Text Printed : "PRESS TO EXIT"
Plate Text Color : BLACK
Plate Button Hole Cutout Size : 22mm
Plate Mounting Holes : 2
Plate Screw Hole Cutout Size : 5mm
Plate Size : 115Hx70Wx1.5D (mm)

Switch Specifications

Series : 800FM
Material : Plastic
Component Type : Pushbutton
Component Style : Flush Type
Button Color : GREEN
Button Diameter: 29.6 mm
Mounting Cutout Hole Size : 22.5 mm
Material – Operator : Zinc Alloy, Die Cast, Chrome Plated
Material – Bezel : Zinc
Material – Body/Housing : Body – Plastic, Housing – Zinc
Material – Spring : Stainless Steel
Operator Action : Momentary
Coupling Pate Included : YES
Contact Block Included : YES
IP Rating : IP66
Illuminated : NO
Tightening Torque Nominal : 4.4 Nm

Relative Humidity : 50% ~ 95% RH
Mechanical Service Life : 10000000 cycles
Shock Acceleration MAX : 100 g
Shock Duration MAX : 11 ms
Operating Temperature : -25° ~ 70° C
Storage Temperature : -40° ~ 85° C
Vibration Acceleration MAX : 10 m/s^2
Vibration Displacement (Peak to Peak MAX) : 1.52 mm
Vibration Duration MAX : 180 Mins
Vibration Frequency – Operational MAX : 2000 Hz
Illuminated : No
Button Size : 29.6DIA x 32D (mm)

Certifications : UR, UL, CSA, CCC, CE, RoHS
Standards Compliance : NEMA ICS-5, UL 508, EN 60947-1, EN 60947-5-1, EN 60947-5-5, IEC 60947-1, ISO 13850
CE Marked : Yes
RoHS Approved : Yes