

SMART9457






Plate Specifications

- Plate Material : STAINLESS STEEL
- Plate Color : SILVER
- Plate style : FLAT
- Plate Text Printed : “PRESS TO EXIT”
- Plate Text Color : BLACK
- Plate Button Hole Cutout Size : 22mm
- Plate Mounting Holes : 2
- Plate Screw Hole Cutout Size : 5mm
- Plate Size : 115Hx70Wx1.5D (mm)

Switch Specifications

- Series : L21AA
- Material : Plastic
- Component Type : Pushbutton
- Component Style : Flush Type
- Button Color : BLACK
- Button Diameter: 29.9 mm
- Mounting Cutout Hole Size : 22 mm
- Material – Operator : Plastic
- Material – Bezel : Plastic
- Material – Body/Housing : Plastic
- Material – Spring : Stainless Steel
- Operator Action : Momentary
- Coupling Pate Included : YES
- Contact Block Included : YES

- IP Rating : IP65
- Illuminated : NO
- Tightening Torque Nominal : 3 Nm
- Relative Humidity : 50% ~ 95% RH
- Operating Temperature : -25° ~ 70° C
- Storage Temperature : -40° ~ 70° C
- Vibration Acceleration MAX : 10 m/s²
- Vibration Displacement (Peak to Peak MAX) : 1.6 mm
- Vibration Frequency – Operational MAX : 100 Hz
- Button Size : 29.9DIA x 32.5D (mm)
- Certifications : UL, OC/CB, BV IEC
- Standards Compliance : UL 508, CSA 22.2, IEC 60947-5-1, IEC 60947-5-5, IEC 60947-5-4, IEC 60068-2-6