

**NPE-1500-LCD-AU**

**NETYS PE 1500VA USB LCD**



Protection for small office, personal or point-of-sale applications.

**Strong points**

- Ideal and cost-effective protection for SOHO or POS applications
- Easy to use
- A solution for network power cuts and voltage fluctuations
- Simplified connection
- Protection for your data line

**General characteristics**

- Minitower case
- Step Wave, AVR function (Automatic Voltage Regulation)
- Control panel with LCD display
- LOCAL VIEW software for local UPS monitoring
- NTP data line suppressor
- Up to 6 UPS output sockets

**Compliance with standards**

- IEC/EN 62040-1, IEC/EN 62040-2
- AS 62040.1.1, AS 62040.1.2, AS 62040.2
- CE
- RCM (E2376)

**Link to the reference**



<https://apac.socomec.com/en/reference/NPE-1500-LCD-AU>

**Classification**

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149

**Commerce**

Description (240 char.)	NeTYS PE 1500VA/900W 230V 50/60Hz BATTERY INCLUDED WITH AVR, STEPWAVE,LCDPLUGSPROTECTEDRJ45, 1xUSB
Effective date	2015-01-01
Country of origin	CN
Discount Policy	D02
Discount Policy Label	NETYS PE
Length of the product unit	0.205
Width of the product unit	0.145
Depth of the product unit	0.39
Weight	6

**Logistics**

GTIN/EAN	8027122522380
Customs number	8504409590
Weight of the packing unit	6
Length of the packing unit	0.39
Width of the packing unit	0.145
Depth of the packing unit	0.205

**Technical Characteristics**

Depth	390
Height	205
In/out	1/1
Output voltage	230
Rated frequency	50/50
Width	145
Sn	1.5
Pn	0.9
Conf	M2
Input voltage	230
Rate (min)	1.5
Rate (max)	1.5
Life Time	03-05
Typical Backup Time	3
Configuration	Line-Interactive UPS with AVR