

CAT6 UTP Slim Patch Cable


W26XX



FEATURES

- All Datamaster® network patch cables are Fluke® tested and are manufactured to exceed Australian standards.
- ISO/IEC 11801 Category 6. TIA/EIA-568-C.2 Category 6 compliant
- Cat6 standard provides performance up to 250MHz and is suitable for fast ethernet and gigabit ethernet plus other network protocols that are backward compatible with Cat5/5e and Cat3 standards
- Slim 3.6mm diameter, 40% smaller than standard patch cable
- Flexible; able to bend at a tight radius
- Ultra slim circumference allows for greater air circulation in crowded server rooms
- Perfect cable when space is limited
- Made from 100% oxygen-free copper
- LSZH jacket
- Unshielded twisted pair (UTP)
- 4 twisted pairs (8 multi-strand connectors) T568A colour code
- RJ45-RJ45 connectors; high quality injection moulded for outstanding strain relief
- 50µm gold Category 6 compliant 2-row (staggered pin) plug
- Snagless boots
- Supplied in Datamaster® hang-cell bags
- 5-year limited warranty
- Custom-made cables are our specialty from custom lengths and colours to customer branded printing, contact us to discuss your needs.

DESIGN & CONSTRUCTION



To view Access' extensive ranges go to: www.accesscomms.com.au

Sydney (Head Office)
Brisbane Office
Melbourne Office
Adelaide Office

Unit 1, 29 Prince William Drive, Seven Hills NSW 2147
28 The Gateway, Broadmeadows VIC 3047
71 Anzac Highway, Ashford SA 5035

Phone: (02) 9414 8888
Phone: (07) 3308 5555
Phone: (03) 9330 8333
Phone: (08) 8338 5540

sales@accesscomms.com.au
brisbane@accesscomms.com.au
melbourne@accesscomms.com.au
adelaide@accesscomms.com.au

CAT6 UTP Slim Patch Cable

W26XX

1	Cable	UTP CAT6 CABLE 4P * 28AWG
2	Connection	P1 & P2 : 8P8C PLUG, LONG BODY, GOLD PLATED
3	Jacket material	LSZH, BLUE COLOUR
4	Packing	Flat patch cable packed in one polybag
5	Cable Printing	DATAMASTER E4073 VERIFIED CAT6 PATCH CORD ANSI/TIA 568 A/B/568C.2 #28AWG 4PR

CHARACTERISTICS

COLOUR	LENGTHS	SKUS
BLUE	0.25m, 0.5m, 1.0m, 1.5m, 2.0m, 3.0, 5.0m, 10.0m	W2640SLIBLU, W2650SLIBLU, W2648SLIBLU, W2651SLIBLU, W2652SLIBLU, W2653SLIBLU, W2655SLIBLU, W2660SLIBLU
YELLOW	0.25m, 0.5m, 1.0m, 1.5m, 2.0m, 3.0, 5.0m	W2640SLIYEL, W2650SLIYEL, W2648SLIYEL, W2651SLIYEL, W2652SLIYEL, W2653SLIYEL, W2655SLIYEL
GREEN	0.25m, 0.5m, 1.0m, 1.5m, 2.0m, 3.0, 5.0m	W2640SLIGRN, W2650SLIGRN, W2648SLIGRN, W2651SLIGRN, W2652SLIGRN, W2653SLIGRN, W2655SLIGRN
PINK	0.25m, 0.5m, 1.0m, 1.5m, 2.0m, 3.0, 5.0m	W2640SLIPNK W2650SLIPNK, W2648SLIPNK, W2651SLIPNK, W2652SLIPNK, W2653SLIPNK, W2655SLIPNK
RED	0.25m, 0.5m, 1.0m, 1.5m, 2.0m, 3.0, 5.0m	W2640SLIRED W2650SLIRED, W2648SLIRED, W2651SLIRED, W2652SLIRED, W2653SLIRED, W2655SLIRED
WHITE	0.25m, 0.5m, 1.0m, 1.5m, 2.0m, 3.0, 5.0m	W2640SLIWHI W2650SLIWHI, W2648SLIWHI, W2651SLIWHI, W2652SLIWHI, W2653SLIWHI, W2655SLIWHI
BLACK	0.25m, 0.5m, 1.0m, 1.5m, 2.0m, 3.0, 5.0m	W2640SLIBLK W2650SLIBLK, W2648SLIBLK, W2651SLIBLK, W2652SLIBLK, W2653SLIBLK, W2655SLIBLK

COMPLIANCE

- RoHS III EU/2015/863
- REACH SVHC x 219 (EC 1907/2006)
- ISO/IEC 11801 Category 6
- TIA/EIA-568-C.2
- AS/CA S008:2020



COLOURS



To view Access' extensive ranges go to: www.accesscomms.com.au

Sydney (Head Office)
Brisbane Office
Melbourne Office
Adelaide Office

Unit 1, 29 Prince William Drive, Seven Hills NSW 2147
28 The Gateway, Broadmeadows VIC 3047
71 Anzac Highway, Ashford SA 5035

Phone: (02) 9414 8888
Phone: (07) 3308 5555
Phone: (03) 9330 8333
Phone: (08) 8338 5540

GREEN

RED

sales@accesscomms.com.au
brisbane@accesscomms.com.au
melbourne@accesscomms.com.au
adelaide@accesscomms.com.au