

Tagit-M26-R2 Reader

Tagit-M26-R2 mullion reader, it reads tagit memory, site code and card number range, 26 bit Weigand format, Wallmount. L86 x W37 x H10 (mm) with three LED, the reading distance is about 5cm.



Specifications

| | |
|-----------------------|-------------------------------------------------|
| Power Supply | 6 - 12V DC |
| Current | >200 mA |
| Frequency | 13,56 MHz |
| Protocol | ISO/IEC 15693 |
| Response time | <100 ms |
| Output | Wiegand 26 |
| Card Compatibility | TI 2048 and all ISO/IEC 15693 compatible cards. |
| Read Range | Up to 5cm |
| Cable Distance | >100m, 22AWG cable |
| Environmental | IP65 |
| Operating Temperature | -20°C ~ 60°C |
| Dimensions | L86 x W37 x H10 (mm) |
| Weight | 68g |

Wiring Guide

| | |
|-------------|-------------------|
| Wire Colour | Signal Definition |
| RED | 12V+ DC |
| BLACK | GND |
| GREEN | WIEGAND DATA 0 |

| | |
|--------|-----------------------------|
| WHITE | WIEGAND DATA 1 |
| Orange | *LED, low voltage enable |
| YELLOW | *BUZZER, low voltage enable |
| BROWN | N/A |
| BLUE | N/A |

* Optional connection