

# Intercom Viewer

## UA-Intercom-Viewer

### Datasheet

#### Overview

Dimensions: 135 x 185 x 32 mm (5.3 x 7.3 x 1.3")

Mobile Unlock ✓

NDAA Compliant ✓

UL 294 Level

- Destructive attack: Level I
- Line security: Level I
- Endurance: Level I
- Standby power: Level I

#### Mechanical

Weight: 168 g (5.9 oz)

Enclosure Material: Glass, polycarbonate

Mount Material: Aluminum alloy

Mounting Wall: (Included) Gang box mount (Optional)

#### Hardware

Indoor and Outdoor Use: Indoor only

Ambient Operating Temperature: 0 to 40° C (32 to 104° F)

Ambient Operating Humidity: 5 to 95% noncondensing

Networking Interface: (1) 10/100 Mbps RJ45 port

Connectivity: Ethernet

Power Method: PoE UL 294 Power-limited Class 2 PSU UL 60950-1/62368-1 LPS/PS2 PSU

Max. Power Consumption: 5W

Supported Voltage Range: 44—57V DC

Display: 127 mm (5") diagonal

Touch Screen Technology: Capacitive multi-touch

Display Luminance: 300 nits (Typical)

Screen Orientation: Portrait

Resolution: 1280 x 720 px

Microphone ✓

Speaker✓

Buttons: (1) Factory-reset

PoE Cabling Requirements: Cat 5e cabling is the minimum performance category recommended. The performance category utilized should match the transmission speed required at the installation site. The minimal conductor gauge permitted to connect between the PSE or power injector and the PD shall be 26 AWG (0.13 mm<sup>2</sup>) for patch cords; 24 AWG (0.21 mm<sup>2</sup>) for horizontal or riser cable.

UL 294 Statement: Compliance with IEEE 802.3 specifications was not verified as part of UL 294. The equipment is intended to comply with the section of the National Electrical Code, ANSI/NFPA 70, Article 725.121, Power Sources for Class 2 and Class 3 Circuits.

CAN/ULC-60839-11-1 Grade: Grade assignment: I

Certifications: CE, FCC, IC, UL 294, CAN/ULC-60839-11-1

Document number, and issue date and/or revision level: UA-Intercom-Viewer, V01

## **Software**

Management Application: Access

Software Information: The software version can be checked at <https://unifi.ui.com>