


Dimensions	135 x 185 x 32 mm (5.3 x 7.3 x 1.3")
Mobile Unlock	✓
NDAA Compliant	✓
UL 294 Level	Destructive attack: Level I Line security: Level I Endurance: Level I Standby power: Level I



▲ Mechanical

Weight	168 g (5.9 oz)
Enclosure Material	Glass, polycarbonate
Mount Material	Aluminum alloy
Mounting	Wall (Included) Gang box mount (Optional)

▲ Hardware

Indoor and Outdoor Use	Indoor only
Ambient Operating Temperature	0 to 40° C (32 to 104° F)
Ambient Operating Humidity	5 to 95% noncondensing
Networking Interface	(1) 10/100 Mbps RJ45 port
Connectivity	Ethernet



Power Method	PoE UL 294 Power-limited Class 2 PSU UL 60950-1/62368-1 LPS/PS2 PSU
Max. Power Consumption	5W
Supported Voltage Range	44—57V DC
Display	127 mm (5") diagonal
Touch Screen Technology	Capacitive multi-touch
Display Luminance	300 nits (Typical)
Screen Orientation	Portrait
Resolution	1280 x 720 px
Microphone	✓
Speaker	✓
Buttons	(1) Factory-reset

PoE Cabling Requirements

Compliance with IEEE 802.3 specifications was not verified as part of UL 294.

The equipment is intended to comply with the section of the National Electrical Code, ANSI/NFPA 70, Article 725.121, Power Sources for Class 2 and Class 3 Circuits.

Cat 5e cabling is the minimum performance category recommended. The performance category utilized should match the transmission speed required at the installation site. The minimal conductor gauge permitted to connect between the PSE or power injector and the PD shall be 26 AWG (0.13 mm²) for patch cords; 24 AWG (0.21 mm²) for horizontal or riser cable.

UL 294 Statement

CAN/ULC-60839-11-1 Grade

Certifications

Document number, and issue date and/or revision level

Grade assignment: I

CE, FCC, IC, UL 294, CAN/ULC-60839-11-1

UA-Intercom-Viewer, V01

▲ Software

Management Application

Access

Software Information

The software version can be checked at <https://unifi.ui.com>