

G6 Pro Turret

UVC-G6-Pro-Turret

Overview

Dimensions

Ø117.2 × 116.5 mm (Ø4.61 × 4.59")

IR Night Vision

40 m (131 ft)

Zoom Mode

2.36x Optical

Face Recognition

✓

License Plate Recognition

✓

Smart Detections (People, Vehicles, Animals)

✓

Resolution

4K

Networking Interface

GbE RJ45 port

Field of View

Wide: H: 113.8°, V: 61.9°, D: 134° Tele: H: 45.5°, V: 25.8°, D: 52°

Audio

Two-way audio

Weatherproofing

IP66

Tamper Resistance

IK04

Mounting

Ceiling, Wall mount (Included) Arm, Pendant mount, Junction box (Optional)

Performance

Networking Interface

GbE RJ45 port

Video

Image Settings

Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay, HDR

Max. Frame Rate

30 FPS

Resolution

8MP 3840 x 2160 (16:9)

Optics

Sensor
1/1.2" 8MP
Lens
F 5.85-13.8 mm; ƒ/1.5-ƒ/2.9
Night Mode
Built-in adaptive IR LED illumination and IR cut filter

Hardware

Max. Power Consumption
15W
Supported Voltage Range
42.5—57V DC
Power Method
PoE+
Processor
Quad core Arm® Cortex®-A53 based chip
Weight
1.2 kg (2.6 lb)
Enclosure Material
Aluminum alloy, polycarbonate
Expansion Slot
MicroSD card
Button
(1) Factory-reset
Cable
Cable Connector Type
RJ45
Cable Diameter
4.5 mm (0.2")
Cable Length
30 cm (1 ft)
Jacket Enclosure Dimensions
Ø20 x 70.55 mm (Ø0.8 x 2.8")
Jacket Enclosure Material
Thermoplastic elastomer, polycarbonate, silicone Rubber
Ambient Operating Temperature
-30 to 50° C (-22 to 122° F)
Ambient Operating Humidity
0 to 90% noncondensing
NDAA Compliant
✓
Certifications
CE, FCC, IC