

UTP Category 5E Cables

Content of Data Sheet			
Product model	CAB-LC5E		
Product specification	Quality verified by latest standard AS/CA S008:2020		
Test Standard	ISO/IEC11801 、 TIA-568-C.2、 IEC61156-6		
Conductor	Material	Solid-Bare Copper	
	AWG	25	
	Nom.O.D.(mm)	0.45±0.005 mm	
	DC resistance	≤115 Ω/km	
Insulation	Material	HDPE	
	Thickness	0.17±0.01 mm	
	Diameter	0.81±0.05 mm	
	Color	Blue/White- Blue	Green/White-Green
		Orange/White-Orange	Brown/White-Brown
Pitch	Offset pitch	≤25 mm	
	Cable pitch	≤140 mm	
Sheath	Material	PVC(complies RoHS/REACH)	
	External O.D.	4.7±0.3 mm	
	Color	CAB-LC5E-BL: Blue CAB-LC5E-GY: Gray(RAL7046)	
	Tensile strength	>13.5 Mpa	
	Thickness	0.55±0.05 mm	
Surface Printing	Letter height	3.0±0.3 mm	
	Color	Black	
	Print error & Space	1±0.005 m	

	Case number	Yes
Packing	Packing	Carton + Plastic shaft
	Color packing dimension	297mm*257mm*310mm
Packing length	305±1 m	
Rip-cord	Yes	
Ambient temperature	-20°C ~ 60°C	

Zhejiang Uniview Technologies Co.,Ltd.

No.369,Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, Zhejiang Province, China(310051)

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2011-2023 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.