

UTP Category 6 Cables

Content of Data Sheet			
Product model	CAB-LC6		
Product specification	Quality verified by latest standard AS/CA S008:2020		
Test Standard	ISO/IEC11801、TIA-568-C.2		
Conductor	Material	Solid-Bare Copper	
	AWG	24	
	Nom.O.D.(mm)	0.52±0.03 mm	
	DC resistance	≤95 Ω/km	
Insulation	Material	HDPE	
	Thickness	0.2±0.02 mm	
	Diameter	0.93±0.05 mm	
	Color	Blue/White- Blue	Green/White-Green
		Orange/White-Orange	Brown/White-Brown
Pitch	Offset pitch	≤20 mm	
	Cable pitch	≤120 mm	
Sheath	Material	PVC(complies RoHS/REACH)	
	External O.D.	5.8±0.3 mm	
	Color	CAB-LC6-BL: Blue CAB-LC6-OG: Orange	
	Tensile strength	>13.5 Mpa	
	Thickness	0.6±0.05 mm	
Surface Printing	Letter height	3.0±0.3 mm	
	Color	Black	
	Print error & Space	1±0.005 m	
	Case number	Yes	
Packing	Packing	Carton + Plastic shaft	

	Color packing dimension	331mm*255mm*338mm		
Packing length	305±1m			
Rip-cord	Yes	Crossing backbone	Yes	
Ambient temperature	-20°C ~ 60°C			

Zhejiang Uniview Technologies Co.,Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2011-2018 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.