

Disk Enclosure

DEU1016-B




Features

- High density. The innovative enclosure with 477mm depth and 3U height that holds up to 16 disks, is space-saving and applicable to the standard rack-mounted scenarios.
- Power protection. Disk powered on sequentially during system startup, protection from impulse current.


Specifications

Hard Disk	Description
SATA	16 SATA Interfaces
Capacity	Up to 16TB for each disk
External Interface	Description
miniSAS	1
RS232	1
Power Supply	AC 100~240V
Working Environment	Description
Working Temperature	-10° C ~ + 55° C (+14° F ~ +131° F)
Working Humidity	5%~95% RH (non-condensing)
Power Consumption(With HDD)	< 160W(With 16 HDDs)
Dimensions	Description
Weight(Without HDD)	< 10Kg (22lb)
Dimensions	482mm × 477mm× 131mm (19.0"×18.8"×5.1")
Height	3U

Dimensions



Rear Panel



Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.