## **Unmanaged Ethernet PoE Switches**

#### NSW2020-6T-POE-IN-V2



#### Features

- Multiple working modes to address your business needs: Default (Normal mode), EXTEND (Surveillance mode)
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

### Specifications

Hardware Specification	Description
Ports Type	6 imes100Mbps network ports (RJ45), including 4 PoE ports
Standards	IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at
Switching capacity	1.2Gbps
Packet Buffer	570K bit
Forwarding performance	0.90Mpps
MAC	2К
Prior Ports	1~2
Power Supply	AC100-240V, 50/60Hz

# UNV

Max.PoE Power	Max capacity:65W Max capacity for single port: 30W 802.3at/af Mode A: (1/2+, 3/6-), Mode B: (4/5+, 7/8-)
Storage Temperature	-40 °C ~ 70 °C
Operating humidity	10% $\sim$ 90% (noncondensing)
Cooling Fans	0
Weight	0.65KG
Dimensions (W $\times$ D $\times$ H)	169*132*40mm
Storage humidity	5% $\sim$ 90% (noncondensing)
Operating temperature	0 °C ~ 40 °C (32 °F ~ 104 °F)
Indicator	POWER Off: No AC input; Power On (Green): Normal power input; Power On (Yellow): The total PoE power is higher than 85% of the total power of the device; No PoE Indicator; LINK/ACT Off: No link; LINK/ACT Steady on: Linked; LINK/ACT Flashing: Transmitting data
Working Mode	Default(Normal mode) : All ports can communicate with each other.; EXTEND(Surveillance mode): Transmission distance up to 250 meters.
Max.Power	75W

#### **Ordering Info**

Product Model	Description
NSW2020-6T-POE-IN- V2	UNV NSW2020-6T-POE-IN-V2 Unmanaged Ethernet Switch(PoE)

#### Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

http://www.uniview.com

©2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.